



Plastic Trends
Injection **molded**
fittings have
Triple
Certification
listing



PVC Solvent Weld Sewer Fittings SDR 35 Injection Molded in Sizes 3" - 12" (Fabricated in Sizes 10" - 24")

Features

- Safe for the Most Demanding Environments
- Tough for the Harshesht Work Sites
- Quick and Easy Installation

Plastic Trends has the broadest product offering of Solvent Weld sewer fittings in the industry. Conform to all municipal, federal, and military requirements. They are tested for joint tightness, internal stress and dimensional stability. The "P" Series is engineered for the harsh environment of construction shipping, handling and installation.

Square X™ Countersunk Threaded Plug

SquareX™ is a major advance in countersunk threaded plug design. It features a unique molded-in shape and installs in seconds. Two standard screwdrivers provide plenty of leverage to tighten or loosen the plug. PVC threaded plugs are notorious for being difficult to remove and are often destroyed in the process. SquareX significantly improves the removal process and reduces the potential for breakage.

FlushMount™ Downspout Adapters

FlushMount™ lets you install pipe right up against the wall. They connect a downspout to either a smooth wall sewer pipe or corrugated drain pipe. Available in 3", 4" and 6" sizes.

Certifications

Plastic Trends Solvent Weld sewer fittings are third party tested and listed by NSF, UPC, and CSA to meet specifications defined in ASTM D3034 & CSA B181.2.



Square X™ countersunk threaded plug improves the removal process and reduces the potential for breakage.

**PVC Solvent Weld
Sewer Fittings SDR 35**
Injection Molded in sizes 3" – 12"
(Fabricated in sizes 10" - 24")

Short Form Specifications

4" through 12" injection molded solvent weld SDR 35 sewer fittings shall be manufactured in accordance with ASTM D 3034 and CSA B182.2. They shall be molded from virgin PVC compound having a minimum cell classification of 12454-B in accordance with, and certified by the National Sanitation Foundation (NSF), to meet ASTM D 1784. Solvent weld SDR 35 sewer fittings shall be certified by the National Sanitation Foundation (NSF) to meet ASTM D 3034 and, in applicable configurations by the International Association of Plumbing and Municipal Officials (IAPMO) to meet ASTM D 3034, and by the Canadian Standards Association (CSA) to meet CSA B182.2.



Plastic Trends, Inc.
56400 Mound Road
Shelby Twp., MI 48316
586.781.2700 • 800.232.5690
Fax: 586.781.0888
www.plasticrends.com



Configurations Available

TEE HxHxH	TEE HxSxH	2-WAY CLEANOUT HxHxH	2-WAY CLEANOUT HxHxDWV H
CLEANOUT TEE HxHxFIPT	SANITARY TEE HxHxH	SANITARY TEE HxSxH	WYE HxHxH
WYE HxSxH	DOUBLE WYE HxHxHxH	DOUBLE WYE HxSxHxH	COMBO WYE & 1/8 BEND HxHxH
1/4 BEND LONG TURN HxH	1/4 BEND LONG TURN HxS	1/4 BEND HxH	1/4 BEND HxS
1/8 BEND HxH	1/8 BEND HxS	1/16 BEND HxH	1/16 BEND HxS
CONCENTRIC REDUCER COUPLING HxH	CONCENTRIC REDUCER BUSHING SxH	COUPLING HxH	CAP H
THREADED PLUG MIPT	COUNTERSUNK PLUG MIPT	MALE ADAPTER HxMIPT	FEMALE ADAPTER HxFIPT
FITTING CLEANOUT ADAPTER SxFIPT	DRAIN GRATE	DOWNSPOUT ADAPTER FLUSH MOUNT	IN-LINE BACKWATER VALVE HxH
TERMINAL BACKWATER VALVE HxH			